# Material Safety Data Sheet (MSDS)

**Series:** #0809/01, #0829/01 (All Labels)

NFPA Rating: HMIS Rating: 0-1-0

				HMIS Rating:	0-1-0-	В		
The second second	SECTION I				EMERGENCY TELEPHONE NO.			
TRADE NAME (IF NONE, PUT CHEMICAL)	100% Heat Resistant RTV Silicone Sealant			(	(918) 825-5744 (24 Hrs.)			
CHEMICAL NAME AND SYNONYMS				* * *			<del></del>	
MANUFACTURER'S NAME AND TELEPHONE NO.	Red Devil, Incorporated	(9	18) 825-5744	<u> </u>			**** · · · · · · · · · · · · · · · · ·	
ADDRESS (Number, Street, City, State, Zip Code)	One Webb Street, Pryor, Ok	lahoma 743	61					
SECTION II - HAZARDOUS INGREDIENTS				%	TLV	PEL	UNITS	
PRODUCT CONSISTS OF:								
Silica * * [68855-54-9] (as Amorphous silica, total dust)				11	10	7.3	mg ma	
Ethyltriacetoxysilane [01768-97-79] * * * *				2	10	10	ppm	
Methyltriacetoxysilane [4253-34-3] ****				2	10	10	ppm	
Iron (III) Oxide * * [1309-37-1] - (as nuisance particulate, total)				10	5	10	mg·m3	
Non-hazardous ingredients*				≥75	NA	NA		
****Comment:	particulates unlikely due to product observe limits for acetic acid, for vater or humid air.	med during cu	ring	T.A.				
	SECTION III - PHYSICAL DA							
BOILING POINT ('F)	NE		PERCENT VOLATILES		>1			
VAPOR PRESSURE (MM Hg.)	NE		BY VOLUME (%)		< 5			
VAPOR DENSITY (AIR=1)	>1		рН			NE		
SOLUBILITY IN WATER	Insoluble		EVAPORATION RATE		NA			
APPEARANCE AND ODOR	Thick liquid; slight vinegar (	odor						
<u> </u>	SECTION IV - FIRE	AND EX	PLOSION H	AZARD	DATA			
FLASH POINT (Method used)	>200°F	>200°F FLAMMABLE				NE U	EL NE	
EXTINGUISHING MEDIA	Carbon dioxide or foam							
SPECIAL FIRE FIGHTING PROCEDURES	No special procedures required							
UNUSUAL FIRE AND EXPLOSION HAZARDS	None known							

# SECTION V - HEALTH HAZARD INFORMATION

#### SYMPTOM/EFFECTS OR OVEREXPOSURE

Eye, nose and throat irritation. Possible skin irritation.

FIRST AID

#### EYES

Immediately flush eyes with large amounts of water while holding the eyelids open. Get medical attention if irritation persists.

#### SKIN

Wipe material from skin with cloth or paper towel, then wash exposed area with soap and water. Get medical help if irritation persists.

#### INHALATION

Move victim to fresh air. Get medical help if irritation persists.

## INGESTION

Contact local poison control center or physician IMMEDIATELY!!

# **SECTION VI - REACTIVITY DATA**

#### STABILITY

Normally stable. Avoid extreme heat

#### INCOMPATIBLE MATERIALS

Moisture will release acetic acid vapor

## HAZARDOUS DECOMPOSITION PRODUCTS

Silicon dioxide, Carbon monoxide, Carbon dioxide, traces of formaldehyde

# SECTION VII - SPILL OR LEAK PROCEDURES

## PROCEDURES

Wear personal protective equipment (See Section VIII). Clean up with absorbent material.

#### WASTE DISPOSAL METHOD

Dispose of in accordance with Local, State and Federal regulations.

# SECTION VIII - SPECIAL PROTECTION INFORMATION

#### RESPIRATORY

Not normally required. If TLV is exceeded, or for symptoms of overexposure, wear a NIOSH-approved respirator for organic vapors.

## EYEWEAR

Wear safety glasses.

## CLOTHING/GLOVES

Not normally required; in situations of extended skin contact, neoprene or other chemical resistant gloves are recommended.

## VENTILATION

Local exhaust may be necessary under some handling/use conditions.

## SECTION IX - SPECIAL PRECAUTIONS

Store in a closed container in dry area. NOTE: Do not weak vapor may become trapped under lenses. This product does lill and 40 CFR 372.65. This product does not contain cools.

APPROVAL

NAM

7614 B

taile applying this material; as acetic acid (cettients listed in Section 313 of SARA Title

Treated Landing BENARC, N

4627

DATE

The information contained herein has been developed based upon current evailable sciently state from the many be developed by time some may render the conclusions of the warr obsolete. Therefore, no warranty is extended as to the applicability winton a vio the user's intended purpose.