Supplier:
Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106
Tolonbone: 1.87 Permate

**Telephone: 1-87-Permatex** 

(877) 376-2839

# **Material Safety Data Sheet**

1. PRODUCT IDENTIFICATION

Product Name: 765-2657 NA GRINDING - WATER 3OZ

Item No: 39835

Product Type: Sharpening compound

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:			
Water 7732-18-5	>50					
TRIETHANOLAMINE 102-71-6	1-10	5 mg/m3 TWA				
SILICON CARBIDE 409-21-2	>3	10 mg/m3 total dust	15 mg/m3 total dust; 5 mg/m3 resp dust			
CARBOMER 9003-01-4	<3	10 mg/m3 TWA	5 mg/m3 (dust) TWA			

## 3. HAZARDS IDENTIFICATION

Toxicity: Harmful if swallowed. May cause eye, skin and respiratory irritation.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation.

Signs and Symptoms of Exposure: May cause redness to eyes and irritation to nasal passages. May cause skin irritation. Moderately

toxic if swallowed. Irritating to mouth, throat and stomach with nausea.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
SILICON CARBIDE 409-21-2	>3		Group A4 Not classifiable	

Medical Conditions Recognized as Being Preexisting pulmonary and dermatological disorders Aggravated by Exposure:

## 4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If

breathing is difficult give oxygen. Get medical attention.

Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical

attention.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical

attention if irritation persists.

## 5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Does not flash

Recommended Extinguishing Media: None - does not burn.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on

flames but should be used to keep fire-exposed containers cool.

Hazardous Products Formed by Fire or Oxides of carbon.

Thermal Decomposition:

Unusual Fire/Explosion Hazards: Closed containers may rupture or explode when exposed to extreme heat. Irritating or toxic gases or

**765-2657 NA GRINDING - WATER 30Z Product Name:** 

Item No: 39835

fumes may be generated by thermal decomposition or combustion.

Not determined. **Lower Explosive Limit:** Not determined. **Upper Explosive Limit:** 

### ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Reclaim clean material. Contaminated material should be swept or shoveled into appropriate waste

container for proper disposal.

## 7. HANDLING AND STORAGE

Storage: Store away from heat.

Handling: Avoid prolonged skin contact. Keep away from eyes. Do not take internally. Wash hands before

eating and smoking.

## **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Safety glasses Eyes: Impermeable gloves Skin:

Ventilation: General ventilation is usually adequate.

Not normally necessary. **Respiratory Protection:** 

## PHYSICAL AND CHEMICAL PROPERTIES

Gray liquid Appearance: MILD Odor:

Not determined. **Boiling Point (°F):** Unknown pH: Moderate Solubility in Water: 1.309 Specific Gravity:

VOC Content(Wt.%): Not determined Vapor Pressure: Not Determined Vapor Density (Air=1): Lighter than air

Slower than butyl acetate **Evaporation Rate:** 

#### 10. STABILITY AND REACTIVITY

Stable at normal conditions **Chemical Stability:** 

**Hazardous Polymerization:** WILL NOT OCCUR None known Incompatabilities: **Conditions to Avoid:** High temperatures. Oxides of carbon. Hazardous Products Formed by Fire or

**Thermal Decomposition:** 

## 11. TOXICOLOGICAL INFORMATION

See Section 3

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.

NH - Not a RCRA Hazardous Waste Material **US EPA Waste Number:** 

## 14. TRANSPORT INFORMATION

**DOT (49CFR 172)** 

**Domestic Ground Transport** 

**DOT Shipping Name:** Unrestricted **Hazard Class:** NONE **UN/ID Number:** None **Marine Pollutant:** None

Product Name: 765-2657 NA GRINDING - WATER 3OZ

Item No: 39835

**IATA** 

Proper Shipping Name: Unrestricted
Class or Division: None
UN/NA Number: NONE

**IMDG** 

Proper Shipping: Unrestricted Hazard Class: None UN Number: None

## 15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical. NONE

INOINE

#### **CALIFORNIA PROP 65:**

No California Prop 65 chemicals are known to be present.

#### **TSCA Inventory Status:**

All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 0, REACTIVITY 0
Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 0, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd Health and Safety Manager

Company: Permatex. Inc. 10 Columbus Blvd. Hartford, CT 06106

**Telephone Number: 1-87-Permatex (877) 376-2839** 

**Revision Date:** 01/14/2002

Revision Number: 1